

Multan® 77-4 The Specialist

Innovation*

Multan



Multan® 77-4 High performance cutting fluid with a patented emulsifier system

Henkel

Multan® 77-4 offers the following benefits:

- High level of bacterial stability through the use of top quality raw materials
- Free of sulphur and phosphorus
- Low drag-out rate as the finely dispersed emulsion runs off the machined parts quickly
- No discoloration of aluminium alloys
- The good washing properties ensure a high level of cleanliness for machined parts, tools and machines

* **Bactericide – free! Makes the addition of bactericide unnecessary, thus facilitating handling of product.**

Very high process economy:

- Low initial fill concentration (5 – 8 %) and significantly lower top-up concentration (0,5 – 2,0 %)
- Very low foaming tendency in all water hardnesses from 5°dH upwards
- Much longer tool-life due to high lubricity (especially with reaming and tapping)

Applications:

Suitable for a broad range of machining operations: reaming, tapping, thread-milling, milling, turning, broaching, drilling, deep hole drilling, circular and flat grinding

Suitable for a broad range of materials: aluminum alloys, steel, high alloy steel, including stainless steel, cast iron and non-ferrous metals



Yes! I want to know more about **Multan® 77-4!**

You are interested in **Multan® 77-4** and want to know more about this product? Fill in the form below and send it back to us today!

I would like:

- to arrange a meeting
- a consultation by phone
- to have detailed technical data sheets
- to run a trial with **Multan® 77-4**

Name

Company

Street

Town

Postal Code

Phone

Fax

E-mail

The information presented herein correspond to our interpretation of certain test results and field experience to date. This information is not to be taken as warranty or representation for which we assume legal responsibility. It is offered solely for your consideration, investigation and verification.

Henkel Norden AB
Copenhagen
Helgeshøj Allé 20-22
2630 Tåstrup
Tel: 43 30 13 01
Fax: 43 30 13 10
www.loctite.dk

Henkel Norden AB,
Oslo
Postboks 6405, Etterstad
0604 Oslo
Tel: 23 37 15 20
Faks: 23 37 15 21
www.loctite.no